



General:

Precast terrazzo one piece products are made of black and white marble chips cast in grey portland cement to produce a compressive strength of not less than 3000 P.S.I., seven days after casting. The terrazzo surface is ground and polished with all air holes and/or pits grouted and the excess removed. Mop service basins are available in custom sizes.

TSB 3000 series is 12" (305) high with 6" (152) drop front. Shoulders shall not be less than 2" (51) wide with 1/2" (13) pitch toward inside. The TSB 3000 series include stainless steel caps on all curbs.

The drain body in mop basins are made of stainless steel cast integrally and provide for a caulked lead connection not less than 1" (25) deep to a 3" (76) pipe.

Installation:

Establish 1/4" (6) clearance between mop service basin and building wall. It is required that the entire area between the mop service basin and the building floor has a 1/2" (13) layer of mortar in order that the mop service basin is level.

Optional stainless steel tiling flanges available.

WITH STAINLESS STEEL CAPS ON ALL CURBS							
MODEL	SIZE	APPROX. SHIP WT.	A	B	C	D	E
TSB-3000	24 x 24 x 12	230 lbs/104 kg	24(610)	24(610)	12(305)	12(305)	15(381)
TSB-3001	32 x 32 x 12	415 lbs/188 kg	32(813)	32(813)	16(406)	16(406)	23(584)
TSB-3002	36 x 36 x 12	470 lbs/213 kg	36(914)	36(914)	18(457)	18(457)	27(686)
TSB-3003	36 x 24 x 12	345 lbs/156 kg	36(914)	24(614)	18(457)	12(305)	27(686)